

## SIMA-tec® Measurement Box



### Dimensions

Size	29 x 33 x 30 cm (L x B x H)
Weight	ca. 12 kg
Material	Aluminium powder-coated
IP Schutzklasse	IP 54

### ELECTRICAL DATA

Connection for power supply	SCHUKO-Plug / 230V / 50 Hz / L/N/PE
-----------------------------	-------------------------------------

### CONNECTORS

Number of channels	8 (optional 12)
SD-port	1
USB-port	1
RJ45 / Ethernet*	1
Digitaler input	1

The SIMA-tec© Measurement Box can be used for a range of applications. In the following, there will be presented three different types of them as examples:

## APPLICATION 1: CUBE 05-VA

In Measurement Box containing sensors\*\*

Pressure	0 - 6 bar	(2 pieces)
Material (parts in contact with medium)	Stainless steel 1.4571	
Flow rate (feed) (Magnetic-inductive)	2 – 180 l/h Minimum conductivity 20 µS/cm	(1 Stück)
Material (parts in contact with medium)	Stainless steel 1.4571 / PEEK / EPDM	
Mass flow meter (permeat) Coriolis measuring principle	0,1 – 10 kg/h No conductivity needed	(1 piece)
Material (parts in contact with medium)	V4a	
Temperature***	0 - 100 °C	(1 piece)
Material (parts in contact with medium)	Stainless steel 1.4571	

## APPLICATION 2: CUBE 80-VA

In Measurement Box containing sensors\*\*

Pressure	0 - 100 bar	(2 pieces)
Material (parts in contact with medium)	Stainless steel 1.4571	
Flow rate (feed) (Magnetic-inductive)	2 – 120 l/h Minimum conductivity 20 µS/cm	(1 Stück)
Material (parts in contact with medium)	Stainless steel 1.4571 / PEEK / EPDM	
Mass flow meter (permeat) Coriolis measuring principle	0,1 – 10 kg/h No conductivity needed	(1 piece)
Material (parts in contact with medium)	V4a	
Temperature	0 - 100 °C	(1 piece)
Material (parts in contact with medium)	Stainless steel 1.4571	

## APPLICATION 3: LRo04

In Measurement Box containing sensors\*\*

Pressure	0 - 6 bar	(2 Stück)
Material (parts in contact with medium)	V4a	
Flow rate (feed) (Magnetic-inductive)	12 – 3000 l/h Minimum conductivity 20 µS/cm 0-70 °C	(1 Stück)
Material (parts in contact with medium)	Stainless steel 1.4571 / PEEK / EPDM	
Flow rate (permeat) (Magnetic-inductive)	2 – 180 l/h Minimum conductivity 20 µS/cm	(1 Stück)
Material (parts in contact with medium)	Stainless steel 1.4571 / PEEK / EPDM	
Temperature	0 - 100 °C	(1 piece)
Material (parts in contact with medium)	Stainless steel 1.4571	

\*\*Analysis of measured data either via "Field Data Management Software" or integration into network feasible

\*\* all sensors are powered by the Measurement Box (Plug and Play)

\*\*\* only for the CUBE 05-VA configured with a stainless steel test cell a temperature measurement is available at the membrane. Otherwise the temperature measurement is realized at the storage tank